

# SETUP INSTRUCTIONS



## STEP 1: GETTING STARTED

Begin by removing the frame from the carry case and placing it on a clean, flat surface.



## STEP 2: CONNECT THE DOTS

Assemble all the Vertical and Horizontal poles, by placing the tapered end of one pole section into the large end of the next while pressing the button snap. It is best to start assembly by connecting all the poles and then attaching the corners.



## STEP 3: ADD SOME CORNERS

Horizontal Curve, Vertical Curve, and Wave Walls – attach corners by inserting into poles using button snaps.

For Flat Walls, tighten the screws using the inner hexagon bolt. (image on below)



## STEP 4: PUT UP SOME SUPPORT

Insert thin pole into holes in center of frame for additional support

# SETUP INSTRUCTIONS



## STEP 5: SLIP & SLIDE YOUR GRAPHIC

Lay frame on the floor with front facing up, and slide graphic from top to bottom. Zip up the graphic.



## STEP 6: NEED SOME FEET?

Flat – attach post and metal foot using screw, and allen key provided

Vertical Curve- attach foot using cotter pin.



## STEP 7: LIGHT IT UP (if you have them)

Ensure the C-clamp is open and place over the top rail of the structure. Close the C-clamp by turning the handle on the back side until secured.



## STEP 8 - VOILÀ

Stand your display and place it in desired location. (This may require 2 people; especially when lights are already placed on frame).